PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵:
A41D 19/00
A1
(11) International Publication Number: WO 92/07480
(43) International Publication Date: 14 May 1992 (14.05.92)

(21) International Application Number: PCT/US91/07709

(22) International Filing Date: 15 October 1991 (15.10.91)

(30) Priority data:

603,078 25 October 1990 (25.10.90) US 720,311 25 June 1991 (25.06.91) US

(71) Applicant: W.L. GORE & ASSOCIATES, INC. [US/US]; 551 Paper Mill Road, P.O. Box 9206, Newark, DE 19714

(72) Inventor: WORDEN, Gregory; 60 Matthew Bathon Court, Elkton, MD 21921 (US).


(74) Agents: SAMUELS, Gary, A. et al.; W.L. Gore & Associates, Inc., 551 Paper Mill Road, P.O. Box 9206, Newark, DE 19714 (US).

(81) Designated States: AT (European patent), BE (European patent), CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent).

Published

With international search report.

(54) Title: WATERPROOF GLOVE HAVING A LINER RETENTION SYSTEM



(57) Abstract

A waterproof glove having a liner retention system comprising an outer shell (C), a waterproof or a waterproof water vapor-transmitting insert (2), and an inner fibrous insulation (A) which entangles with the fibrous backing layer (4) of the water-proof insert (2) to give good liner retention. Useful for ski gloves, mittens, work gloves and the like under severe weather conditions.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	Fl	Finland	ML.	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinca	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL.	Poland
CA	Canada	n	italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CC	Congo	KP	Democratic People's Republic	SE	Sweden
CH	Switzerland		of Korca	SN	Senegai
CI	Côte d'Ivoire	KR	Republic of Korea	SU+	Soviet Union
CM	Cameroon	£l	Liechtenstein	TD	Chad
cs	Czechoslovakia	LK	Sri Lanka	TG	Togo
DE+	Germany	LU	Luxembourg	US	United States of America
20	December	MC	Managa		

⁺ Any designation of "SU" has effect in the Russian Federati n. It is not yet kn wn whether any such designation has effect in other States of the former Soviet Union.

τ

1 TITLE OF INVENTION

WATERPROOF GLOVE HAVING A LINER RETENTION SYSTEM

FIELD OF THE INVENTION

The invention relates broadly to lined waterproof gloves or mittens for protection during adverse weather conditions, and particularly to gloves having a waterproof insert and an insulative liner.

BACKGROUND OF THE INVENTION

A glove manufactured for use under severe weather conditions is usually constructed at present with an insulative liner next to the skin of the wearer, which is enclosed in a waterproof insert, and both these layers are enclosed in an outer shell. The insulative liner provides comfort under cold weather conditions and the waterproof insert keeps the insulation of the glove and the hand of the wearer dry. The outer shell provides protection to the inserts and the liner and fashion qualities.

With the introduction of waterproof inserts into gloves certain problems arise. One major problem has been keeping the insert in place between the inner liner, usually the insulation, and the outer shell of fabric and/or leather. The process for stabilizing the insert has become known in the industry as insert retention. Since the only connection point for all three layers is the cuff, the insert floats between the inner liner and outer shell. The insert is not held in place by stitching, because that will violate the integrity of the waterproof membrane. Without the insert firmly held in place, the insert and inner liner can invert upon removal of the hand from the glove. Often the liner and insert cannot be reinverted and the glove can no longer be worn at all. If the liner can be reinverted, the act usually results in the rupturing of the waterproof insert, resulting in a non-waterproof glove.

To ensure the highest quality possible, a method of insert and liner retention is needed for all gloves which are assembled in separate layers.

SUBSTITUTE SHEET

SUMMARY OF THE INVENTION

The present invention comprises hand coverings, i.e. gloves or mittens having a liner of fibrous insulation and a waterproof insert within an outer shell. The shell is usually leather or cloth. The waterproof insert preferably comprises a layer of porous hydrophobic polymeric membrane, which is waterproof to liquid water and which transmits water vapor. Preferably it is expanded polytetrafluoroethylene (PTFE) laminated to or coated with a layer of water vapor-transmitting polyurethane or other polymer: but it may be any waterproof insert, such as neoprene, polyvinyl chloride, rubber, latex, or polyurethane. It can also be a microporous polymer membrane made from polypropylene, polyurethane, or a structure embodying both microporous hydrophobic polymer and hydrophilic polymer embedded in its pores or layered on its surface. The waterproof insert is in turn bonded on the inside by heat or an adhesive to a non-woven or brush woven, entangleable textile fiber scrim which may be polyester or polyamide, for example. The adhesive may be in the form of a liquid or a powdered solid.

It may alternatively be useful to include an entangleable scrim between the outer shell and the waterproof insert. This requires the scrim to be bonded to the outside of the waterproof insert and requires that the shell have an entangleable layer on the inside. Also an entangleable resin layer may be bonded to both the inside and the outside of the waterproof insert so that one side may entangle with the outer shell and the other side with the inner insulation at the same time. The shell may have a rough enough interior surface to entangle with the fibers of the scrim or may have a fibrous or entangleable foam material bonded to its interior surface.

All three layers of the glove construction are held in place by stitching only at the cuff of the glove. In a preferred embodiment, the inner layer is the fibrous insulation, the middle layer comprises the waterproof insert layer (the preferably expanded PTFE layer facing outwardly), and the outer layer comprising the protective shell.

Upon wearing the glove for a short period, it has been discovered that the fibers of the insulation layer will entangle with fibers from the textile scrim layer of the middle layer to an

Ş

extent that it requires several pounds of pull-out strength per glove finger to separate the insulation and the waterproof middle layer from each other. This entanglement results in a glove which will not have its lining invert under normal hand removal procedures.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows the insulation fitting into the waterproof insert, which fits into the outer shell of a glove of the invention.

Figure 2 is a cross-sectional view of a preferred waterproof insert of the glove of the invention.

Figure 3 is a photomicrograph of entangled fibers of the insulation and the inner fabric layer of the waterproof insert of the glove of the invention.

Figures 4, 5, and 6 are cross-sectional views of segments of gloves of the invention which describe alternative arrangements of layers.

DETAILED DESCRIPTION OF THE INVENTION

In terms of the figures, the glove of the invention is now described in detail.

Figure 1 shows how the three principal layers of the invention fit together with the insulation layer \underline{A} fitting inside a middle waterproof water vapor transmitting insert \underline{B} , which in turn fits inside outer protective shell \underline{C} . Layers, \underline{A} , \underline{B} , and \underline{C} when fitted into each other in proper order are joined together by preferably stitching them together at the cuff of the glove as shown at point \underline{I} , as shown on the outside of shell \underline{C} in Figure 1. Shell \underline{C} may be leather or fabric or a combination of both materials, such as in ski gloves or work gloves, for example. The shell fabric may be cotton or synthetic textile material.

Figure 2 displays a cross-sectional view of one variant of the waterproof water vapor transmitting insert \underline{B} portion of the glove of the invention. The waterproof material $\underline{2}$ is on the outside of the insert and is preferably porous expanded PTFE membrane

material, such as disclosed in U.S. Patent Nos. 3,953,566, 3,962,153, 4,096,227, and 4,187,390, assigned to W. L. Gore & Associates, Inc. These materials are well known in the art for being waterproof, but at the same time being capable of transmitting large amounts of water vapor, such as from the skin of a wearer to the outside of an article of clothing containing the materials. Layer 3 is a water vapor transmitting layer of polyurethane polymer bonded to PTFE layer 2 to provide a hydrophilic oil resistant, but water vapor transmitting layer, between the PTFE layer 2 and the skin of a wearer of the glove, such as described in U.S. Patent Nos. 4,194,041 and 4,443,511. Other waterproof and water vapor transmitting materials, such as those described above may be used. A non-woven textile fiber scrim material $\underline{4}$ is bonded to polyurethane layer $\underline{3}$ by preferably heat bonding, although a water vapor transmitting polyurethane adhesive may be used. Material 4 could be substituted by brush-woven fabric as an alternative if such fabric provides enough free fibers such that they will entangle with the fibers of the insulation to the degree necessary to provide adequate insert retention by entanglement and mechanical bonding of the two layers. Examples of suitable layer 4 materials are Lutrabond® laminate of spunbonded polyamide 6 and Cerex® laminate of spunbonded polyamide 6,6. Non-woven polyester fiber materials may also be used as may fibers of glass, rayon, or polypropylene as may carded non-woven materials.

Figure 3 shows a photomicrograph of entangled fibers $\underline{5}$ of scrim layer $\underline{4}$ of the insert and fibers 6 of the insulation.

Figure 4 depicts a cross-sectional view of the glove of Figure 1. A is the fibrous insulation and \underline{C} is the outer protective shell. Insert layer \underline{B} is seen in Figure 4 to comprise waterproof material $\underline{2}$, polyurethane layer $\underline{3}$ and scrim $\underline{4}$.

In Figure 5, \underline{A} is the fibrous insulation, \underline{C} is the shell and $\underline{2}$ is the waterproof layer.

In Figure 6, \underline{A} is the fibrous insulation, \underline{C} is the shell, $\underline{2}$ is the waterproof layer and $\underline{4}$ is the scrim. In this embodiment, the shell contains a fibrous material.

Insulation layer \underline{A} , the innermost layer of the glove, next to the skin of the wearer, may be almost any suitable insulation material known in the art to be useful in insulating gloves.

٤

except those foamed insulating materials which will not entangle with fibers from layer 4 of insert B and material and other organic fibers which mat when wetted. Examples of suitable insulation materials include Thinsulate® polyolefin/polyester, Fiberfill® polyester, Thermolite® polyester. The insulation may be attached to a textile layer to hold the insulation material together against flexing and other forms of wear during use of the glove containing it.

The inventive steps and combinations of materials also apply to mittens as an alternative form of gloves, since they function in the same way as gloves as regards liner retention.

I CLAIM:

- A lined waterproof hand covering comprising in order inside to outside:
 - (a) a layer of fibrous insulation;
 - (b) a waterproof water vapor-transmitting insert comprising
 - (i) an outer porous polymeric membrane bonded to;
 - (ii) a hydrophilic water vapor transmitting polyurethane layer, which is in turn bonded to;
 - (iii) a fibrous textile scrim layer, wherein the scrim is adjacent the fibrous insulation; and
 - (c) an outer protective shell wherein said insulation, said insert, and said shell are attached to each other at the cuff of said glove;

wherein fibers of the fibrous insulation are entangled with fibers of the fibrous textile scrim.

- 2. A hand covering of Claim 1 wherein said attachment to said cuff is by stitching or adhesive.
- 3. A hand covering of Claim 1 wherein said porous polymeric membrane is expanded polytetrafluoroethylene.
- 4. A hand covering of Claim 1, 2, or 3 in the form of a mitten.
- 5. A hand covering of Claim 1, 2, or 3 in the form of a glove.
- 6. A lined waterproof hand covering comprising in order inside to outside:
 - (a) a layer of fibrous insulation;
 - (b) a waterproof insert comprising a porous membrane and a fibrous textile scrim layer bonded to said membrane wherein the scrim is adjacent the fibrous insulation; and
 - (c) an outer protective shell wherein said insulation, said insert, and said shell are attached to each other at the cuff of said glove;


wherein fibers of the fibrous insulation are entangled with fibers of said fibrous textile scrim.

- 7. A lined waterproof hand covering comprising in order inside to outside:
 - (a) a layer of fibrous insulation;
 - (b) a waterproof water vapor-transmitting insert, containing a fibrous textile scrim layer; and
 - (c) an outer protective shell wherein said insulation, said insert, and said shell are attached to each other at the cuff of said glove;

SUBSTITUTE SHEET


6

- wherein fibers of the fibrous insulation or the shell are entangled with fibers of said fibrous textile scrim.
- 8. A hand covering of Claim 1 having an additional layer of textile scrim bonded to the outside of said waterproof insert and an outer protective shell having a roughened interior surface or an entangleable layer bonded to said interior surface.
- 9. A lined waterproof hand covering comprising in order inside to outside:
 - (a) a layer of fibrous insulation;
 - (b) a waterproof insert having a layer of textile scrim bonded to the outside of said insert; and
 - (c) an outer protective shell having a roughened interior surface or an entangleable layer bonded to said interior surface.
- 10. A hand covering of Claims 6, 7, 8 or 9 in the form of a mitten.



Š

2 / 4





F1G.

3 / 4



4 / 4





International Application No

	-	CT MATTER (if several classification symbol	ols apply, indicate all) ⁶	
I. CLASSIF	TCATION OF SUBJE	Classification (IPC) or to both National Classi	fication and IPC	
According t	to International Patent 5 A41D19/00			ļ
Int.CI.	, 2 M4TD13/0			
II. FIELDS	SEARCHED	Minimum Documentat	ion Searchea?	
			sification Symbols	
Classificati	ion System			
Int.Cl.	. 5	A41D		
		Documentation Searched other that to the Extent that such Documents are	n Minimum Documentation Included in the Fields Searched ⁸	
III. DOCU	MENTS CONSIDER	ED TO BE RELEVANT ⁹	12	Relevant to Claim No.13
Category °	Citation of D	ocument, 11 with indication, where appropriate,	of the relevant passages 12	Military of Colors
Х		662 006 (CHARLES ROSS JR) le document and especial	1 5 May 1987	1-10
х	DF.U.8	715 686 (DR N. VOACK) 14 whole document	January 1988	1-10
х	NL,A,6 ANGER)	503 302 (NITEX-SCHAUMSTON 31 May 1966	FFABRIK WOLFGANG	1-10
A	US,A,4 see the	583 248 (J.H. EDWARDS) 22 whole document	2 April 1986	1-10
A	US,A,4 see the	430 759 (D. JACKREL) 14 whole document	February 1984	1-10
"A" d	considered to be of part artier document but pu- illing date lociment which may the which is cited to establi- itation or other special document referring to a where means	general state of the art which is not icular relevance blished on or after the international row doubts on priority claim(s) or sh the publication date of another reason (as specified) un oral disclosure, use, exhibition or to the international filing date but	"T" later document published after the intermor priority date and not in conflict with a cited to understand the principle or theo invention "X" document of particular relevance; the cited cannot be considered novel or cannot be involve an inventive step "Y" document of particular relevance; the cited cannot be considered to involve an inventive an inventive and i	ry underlying the aimed invention considered to aimed invention nitive step when the other such docu- to a person skilled
	TIFICATION	10	Date of Mailing of this International Se	arch Report
Date of the		of the International Search NUARY 1992	0	5 FEB 1992
l _	onal Searching Authori EUROF	ry PEAN PATENT OFFICE	Signature of Authorized Officer VANMOL M.	DO

į

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO. US SA 53115

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 22/01/92

Patent document cited in search report	Publication date	Patent family member(s)		Publication date	
US-A-4662006	05-05-87	None	None		
DE-U-8715686	14-01-88	None			
NL-A-6503302	31-05-66	None			
US-A-4583248	22-04-86	None			
US-A-4430759	14-02-84	US-A- US-A-	4520056 4545841	28-05-85 08-10-85	

FORM POST

For more details about this annex: see Official Journal of the European Patent Hice, No. 12/82